ELECTRIC DOUBLE LAYER CAPACITORS "DYNACAP"



5.5V Miniaturized High Temperature Capacitors

DX

- High temperature type of Series DX.
- •5mm tall. Max. thin profile (H-shaped).
- Miniaturized but can encase up to 0.33F in 11.5×5mm case, and 1.0F in ϕ 19.0×20.5Lmm case.




Marking color: White print on a black sleeve

Specifications

Item	Performance							
Category temperature range (°C)	-10 to +85							
Tolerance at rated capacitance (%)	-20 to +80							
Internal resistance	Rated capacitance (F) 0.047 0.1 0.22 0.33 1							
at 1 kHz	Internal resistance (Ω Max.) 200 150 150 150 75							
Characteristics at high	Percentage of capacitance change Within ±30% of the value at 20°C							
and low temperature	Internal resistance Less than four times of the initial specified value.							
	Test time 1000 hours							
Endurance (85℃)	Percentage of capacitance change Within ±30% of the initial measured value							
	Internal resistance Less than four times of the initial specified value							
Shelf life (85°C)	Test time : 1000 hours ; Same as endurance.							
Applicable standards	Conforms to JIS C5160-1 2009 (IEC 62391-1 2006)							

High temperature

Outline Drawing Unit: mm



ĮF	Part numbering system (example : 5.5V0.1F)						
	DXJ	_	5R5		104		U
	Series code		Max.operating voltage symbol	Terminal code	Rated Capacitance symbol	Additional symbol	

Part number is refer to following table.

Note

Do not apply external force to products or terminals as stress such as twisting, bending, pushing, or falling of such products or terminals may remove the terminals, resulting in an open/short circuit or liquid leakage. Avoid applying excessive heat to capacitors during heating of an adhesive curing oven. For details, refer to the precautions in use of DYNACAP.

Standard Ratings

Max. operating voltage (V)	Rated capacitance (F)	ELNA Parts No.	φD×L (mm)
5.5	0.047	DXJ-5R5V473U	11.5×13.0
5.5		DXJ-5R5H473U	11.5× 5.0
5.5	0.1	DXJ-5R5V104U	11.5×13.0
5.5		DXJ-5R5H104U	11.5× 5.0
5.5	0.22	DXJ-5R5V224U	11.5×13.0
5.5		DXJ-5R5H224U	11.5× 5.0
5.5	0.33	DXJ-5R5V334U	11.5×13.0
0.0		DXJ-5R5H334U	11.5× 5.0
5.5	1	DXJ-5R5V105U	19.0×20.5