DH ELECTRIC DOUBLE LAYER CAPACITORS "DYNACAP"



GREEN CAP **High Temperature Capacitors** 85°C

• High temperature tolerant (-25 to +85°C) and highly reliable.

· Ideal for backing up of controls, electronic rice cooking jars, home bakeries and the like.



 $\langle \Box$




Marking color : White print on an indigo sleeve

Item	Performance						
Category temperature range (°C)	-25 to +85						
Folerance at rated capacitance (%)	-20 to +80						
Internal resistance	Rated capacitance (F)	0.047	0.1	0.22	0.47	0.68	1
at 1 kHz	Internal resistance (Ω Max.)	300	200	120	50	50	30
Characteristics at high and low temperature	Percentage of capacitance change Internal resistance	Within ±30% of the value at 20°C Less than five times of the value at 20°C					
Endurance (85°C)	Test time Percentage of capacitance change	1000 hours Within ±30% of the initial measured value					
	Internal resistance	Less than four times of the initial specified value					
Shelf life (85°C)	Test time : 1000 hours ; Same as endurance.						
Applicable standards	Conforms to JIS C5160-1 2009 (IEC 62391-1 2006)						

Outline Drawing

Unit : mm



Part numbering system (example : 5.5V0.1F)						
	DH	_	5R5	D	104	Т
	Series code	-	Max.operating voltage symbol		Rated capacitance symbol	

Part number is refer to following table.

Standard Ratings

Max. operating voltage (V)	Rated capacitance (F)	ELNA Parts No.	φD×L (mm)
5.5	0.047	DH-5R5D473T	13.5×9.5
5.5	0.1	DH-5R5D104T	13.5×9.5
5.5	0.22	DH-5R5D224T	13.5×9.5
5.5	0.47	DH-5R5D474T	21.5×9.5
5.5	0.68	DH-5R5D684T	21.5×9.5
5.5	1	DH-5R5D105T	21.5×9.5

